

SPOA10-AV

THE ONE LIFT TO SERVICE THEM
ALL WITH INNOVATIVE AV ARMS™



THE HIGHEST CAPACITY
LOW-PROFILE ASYMMETRIC
LIFT AVAILABLE



Model shown:
SPOA10N20MOBL


**Customize SPOA10AV
lifts to fit the needs of
your shop.**

Choose your:

- Adapter type
- Lift height
- Power option
- Lift accessories



THE NEXT EVOLUTION
IN VEHICLE LIFT
TECHNOLOGY IS HERE



THE INDUSTRY'S ORIGINAL
ASYMMETRICAL LIFT FEATURES
ROTARY'S PATENT-PENDING,
ALL-VEHICLE LIFT ARMS.

10,000 lbs. capacity AV ARMS™ lift and
service practically all roadgoing vehicles
on ONE LIFT, including:*

- Battery Electric
- Exotic Low Profile
- Truck Frame
- Unibody Cars & SUVs



WATCH & LEARN!

Scan code to watch
product videos.

*Within the lift's rated capacity

SIMPLY LIFTING EVERYTHING.

YOU WON'T HAVE TO TURN AWAY BUSINESS WITH ROTARY'S AV ARMS™




ULTIMATE LIFTING VERSATILITY

With the shortest arm retraction and largest pickup range of any two-post lift, Rotary's AVARMS™ simplify your shop and give technicians the flexibility and clearance needed to service any vehicle.

EASY SPOTTING & POSITIONING

Rotary's new AVARMS™ allow you to properly lift any vehicle on recommended OEM pickup points. Get more vehicles in the shop and on the lift faster with easy spotting and superior lifting capabilities.

With the industry's lowest profile arm height available of any 10,000 lb. capacity two-post lift, technicians can easily spot lower profile vehicles without worry.




THE LOWEST ADAPTER HEIGHT IN THE INDUSTRY

The outer arm and adapter height are the same measurement reducing any possibility the arm makes contact with vehicle underbodies.



ADJUSTABLE LOW ADAPTER HEIGHT: EASILY SPOT AND LIFT UNIBODY, EXOTIC, AND BATTERY ELECTRIC VEHICLES



The adjustable, low adapter height allows the needed reach to easily spot, lift, and repair unibody, exotic, and battery electric vehicles.

THE ONLY LIFT YOU NEED.

PATENT-PENDING ALL-VEHICLE AV ARMS™

Innovative design streamlines the arm for a simpler fine adjustment of the adapter while maintaining maximum reach and retraction. Engineered, high-strength tapered arm design allows for easier, faster positioning of adapters compared to traditional arm designs.


20% MORE REACH

THAN 3-STAGE ARMS WITH THREAD-UP ADAPTERS

30% LARGER ARM SWEEP

THAN CONVENTIONAL 2-STAGE ARMS WITH FLIP-UP ADAPTERS

SHORTEST ARM RETRACTION IN THE MARKET BY UP TO 9"



LARGEST PICK UP AREA RANGE IN THE MARKET

Substantial maximum reach for lifting trucks and other frame vehicles

COMES STANDARD WITH ADJUSTABLE ROUND, TRUCK & STACKABLE ADAPTER EXTENSIONS

Include two sets (four each) of 3 1/2" and 5 1/4" stackable adapter extensions with storage rack.



ROUND ADAPTERS For lifting unibody and battery electric vehicles.

Set of four polymer pad round adapters thread-up to allow protection of vehicle underbody components or undercoating for no metal on metal contact.



TRUCK ADAPTERS For use on framed vehicles.

Set of four adjustable thread-up adapters with rubber pads for protection of underbody vehicle components or undercoating.



ROTARY[®] BY ROTARY SOLUTIONS

SPOA10-AV 2-POST LIFT


SPECIFICATIONS:

LIFT MODELS

STANDARD POWER		SPOA10N20M0RD SPOA10N20M0BL SPOA10N20M0BK
SHOCKWAVE-EQUIPPED POWER		SPOA10U20M5RD SPOA10U20M5BL SPOA10U20M5BK
MAX RISE*	STANDARD SHOCKWAVE	81 1/2" 84 1/2"
Overall Height		11' 11 1/2" With SHOCKWAVE Power: 12' 5 1/2"
Overall Width		11' 5 1/2"
Drive-Thru Clearance		95 1/4"
Inside Columns		107 1/4"
Front Arm Reach: Min/Max		18 1/2" / 41"
Rear Arm Reach: Min/Max		27 5/8" / 58 1/4"
Min Adapter Height		3 3/8"
Speed of Rise		Standard Power: 45 seconds With SHOCKWAVE Power: 25 seconds**
Speed of Descent		Standard Power: 40 seconds With SHOCKWAVE Power: 19 seconds**
Ceiling Height Minimum		12' / 12' 6" with SHOCKWAVE Power
Min. Bay Size		12' x 24'

* Rise measures the highest position of the adjustable adapters with use of supplied adapter extensions from floor to full cylinder stroke.

**Actual rise and descent times vary depending on vehicle weight. Heights and widths reflect standard settings. Lifts colors are red (RD), blue (BL), or black (BK)



Model shown:

SPOA10U20M5RD

with optional SHOCKWAVE-POWER

Supercharged SHOCKWAVE™ equipped Rotary Lifts are the world's fastest – and only available from Rotary!

Twice as fast than any other standard service lift, Shockwave-equipped lifts are designed specifically for service speed. Watch your productivity increase, the number of service orders increase and be shocked at the increase in revenue!

ADDITIONAL FEATURES

- Original "Double S" column design
- Performance tested to 20,000 lift cycles
- Nationwide support
- ALI Gold Certified



ROTARY SOLUTIONS

To learn more about all of our automotive service and repair solutions or to contact your local distributor, visit us at www.RotarySolutions.com today.

Need assistance or have questions? We're here to help:

800.445.5438 / Sales: insidesales@rotarysolutions.com

Technical Support: LD-techsupport@rotarysolutions.com

ROTARY SOLUTIONS™

2700 Lanier Drive | Madison, IN 47250, U.S.A.

Lit# [Rotary.SPOA10-AV Cutsheet.03.01.2025](#)

©2025 VEHICLE SERVICE GROUP™

All Rights Reserved. Unless otherwise indicated, ROTARY SOLUTIONS™, VEHICLE SERVICE GROUP™, DOVER® and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability.